

CRAMBO MOBILE

Shredder for wood and green waste







komptech.com



OVERVIEW

Low-speed dual-shaft shredder for wood and green waste

The Crambo is one of the best machines there is for shredding all types of wood and green waste. Two slow-running drums with shredding teeth minimize fine particle and noise/dust emissions, and resist contraries. The Crambo enables easy adjustment of the output particle size, by simply exchanging the screen basket to instantly change the particle size. In addition to the proven hydraulic drive, there is a mechanical drive version for top economy. A modern operating console and convenient access to all maintenance points make everyday work very easy.

- High throughput with general-purpose use
- Aggressive feed with long, counter-rotating shredding drums
- Variable particle sizes through simple screen basket change
- Numerous chassis and equipment options

Engine power (kW)

242 447

Max. throughput (t/h)



Gross weight (t)



Wide range of applications

Green waste,

Rootstocks,

Waste wood

forest wood residue

Special applications

2

woody biomass



A high throughput of bulky vegetation is made possible by the generously dimensioned feed area, folding hopper and counter-rotating teeth. Blockages from wet material and high grass content are practically impossible. The teeth clear the screen baskets on every revolution.

If a rootstock fits into the shredding area, it will also go through. The highly effective tooth power offered by the efficient drive, the intense motion of the material and the insensitivity to embedded stones all make the Crambo ideal for this application.

When shredding waste wood, the wear-resistant teeth provide a high level of resistance to contraries. Counter-rotating shafts, together with the special shape of the teeth, produce a perfect feed, even for fractions with high board content.

The innovative shredding concept provides a wide range of application possibilities. Established applications include shredding organic waste for composting, shredding market and food/kitchen waste for fermentation, and preshredding of rotor blades from wind turbines for recycling.





The machine in greater detail

Every Komptech machine meets the highest requirements for dependability and value retention. This is assured by the use of high-quality components, certified production and gapless quality control.

X

02



Screen baskets

Ô)

KOMPTECH CRAMBO

05

00-

(06)

80 | 100 | 125 | 150 | 180 220|250|300|XL

Drum drive

Hydraulic (\Diamond) Mechanical



Power plant

- Powerful Caterpillar diesel engines with the latest exhaust scrubbing
- High-performance cooling system for engine and hydraulics
- Fully encapsulated engine
- compartment to reduce noise emissions

$\cap 4$



Operation

- Operating panel with a 7" high resolution screen and intuitive menu guidance
- Reversing program to adapt to the material and for drum selfcleaning
- Onboard diagnostics, with trouble-shooting integrated into the control system for fast problem solving

02



Drum drive

- Option 1: Hydraulic drive with load-dependent speed regulation • Option 2: Mechanical drum
- (Crambo direct)
 - and engine

05



Ease of use

- Particle size adjustment: Change of screen baskets or change of the entire basket cartridge
- Extremely large 2 m x 3 m feed area
 - material feed

(01)

03



drive with 2-speed transmission

Overload protection for drum



Shredding unit

- Extremely large shredding compartment with two aggresive feed drums
- Wide range of screen baskets available
- Quick-change system for screen basket and tools

• Hydraulic folding hopper for easy

06



Maintenance

- Large service panels for easy access to engine and drum
- All maintenance points (oils, filters, refuelling) externally accessible
- Excellent access to the wide discharge channel through side service doors



Shreds anything

In the generously dimensioned shredding area, two 2.8 metres long counter-rotating shafts provide active feed. The teeth seize the material and press it in a cutting/splitting action against the cutting edge and screen baskets located underneath. Slow turning results in a lumpy shred initially. The shredding drums are effectively protected against wear by armouring in exposed zones.

The material does not exit the shredding area until the particle size matches the hole size of the screen basket, enabling the quantity of shredded material in the desired particle size to be maximized. There is no additional generation of fine fractions, and overlengths are reduced to a minimum.

Options

Shredding drums

Specially developed bearings keep the massive shredding drums securely in place, even under extreme loads. Strong planetary gears boost drive train life, for dependable service through thousands of operating hours.

Teeth

With their carefully designed profile, the drop-forged wear teeth ensure maximum service life and consistent functionality. The all-purpose sickle teeth deliver aggressive feed and good cutting. The planing teeth give good results on waste wood when used with smaller screen baskets. Their shape makes them very long-lived.

Bio cutting unit

This optional cutting unit is ideal for preparing woody biomass for use as fuel. Countercut tools inserted near the central cutting edge give an efficient cut, for finer shredding and the right output particle consistency.

Screen baskets

Screen baskets are tailored to the cutting unit and are available in the sizes most commonly used in practical applications. To replace, activate the button to swivel the screen basket cartridge out hydraulically. Remove the screen basket halves from the cartridge and replace with another screen basket, or exchange the entire screen basket cartridge. Swivel it in again to continue working.







AT WORK

In daily use

Over seven cubic metres hopper volume

Just load material into the big hopper – the machine does the rest. Hydraulically folding hopper sidewalls make the already generous shredding chamber even bigger.

Efficient shredding

You can choose between highly efficient mechanical drum drive with automatic transmission – the Crambo direct – or the proven hydraulic drive with load-dependent speed regulation. The tool-free quick-change system for the screen baskets and reversing programs for the drums adapt the shredding process precisely to the material. Other benefits include contrary recognition as a safety feature and ECO mode as an energy saving function.

Ready for anything

Options let users configure the Crambo for the exact task. Wireless remote control and central lubrication add to ease of use, a moistening system keeps dust down, and an extended discharge conveyor allows high discharge cones. The overbelt magnet can be exactly aligned with the discharge conveyor position, for optimum separation performance.

Mobility the way you need it

On the Hooklift version, a towing setup provides manoeuvrability at the site. The Trailer version has aircushioned axles and positioning capability, to facilitate frequent site changes. The Track version with two-stage drive and extra-wide treads can handle unhardened surfaces.

Always know what's going on

The Connect! app, which is freely usable with every Crambo, enables transparent administration, optimum job planning and remote monitoring of machines. GPS data provides for precise locating, and the data history and data exports offer many possibilities for improving operating economy. NEW: Throughput measurement and evaluation with Connect!.

Functions



Steplessly adjustable drum speed (hydraulic)



programs



Swivel screen basket

MEDIUM

Contrary detection

Operation



Adjustable nopper walls

ECO

ECO Mode



Condition monitoring

Options



Moistering equipment



Adjustable overbelt naanet

Throughput measuremen



The Komptech plus

All-in solutions

From individual mobile machines to complex stationary systems, with us you get the right process solution.

$-\sqrt{}$

Productivity in view

Apps and integrated monitoring let you keep an eye on operating data and economy.



Need-based service

Our maintenance and service agreements, as well as extended warranties, are aligned with your needs.

Overview of our technology

Look here for the newest updates, specifications and more detailed descriptions:

5200

6000



6200

V

Hook (hook lift chassis)



Engine

Model

Manufacturer	Caterpillar	Caterpillar	Caterpillar	Caterpillar	Caterpillar	Caterpillar
Power (kW/HP)	250/340	250/340	328/446	328/446	447/608	447/608

5000

4200

Loading heights

Loading heights (mm)	Hook: 2,396 Trailer: 2,996 Track: 2,898
Discharge heights (mm, 10°-35°)	Hook: 1,520-3,842 Trailer: 1,929-4,250 Track: 1,830-4,151

3400

Shredding unit

Drum drive	hydraulic	mechanical	hydraulic	mechanical	hydraulic	mechanical
Drum rpm	max . 35	20 (1 st speed)	max. 32	22 (1 st speed)	max. 39	28 (1 st speed)
		30 (2 nd speed)		$34 \ (2^{nd} \ speed)$		42 (2 nd speed)
Drum length (mm)	2,820	2,820	2,820	2,820	2,820	2,820
Drum diameter (mm)	610	610	610	610	610	610

Dimensions in transport position/working position (conveyor belt 35°)

Hook – L x B x H (mm)	7,290 x 2,500 x 2,766 12,292 x 3,290 x 3,842
Trailer – L x B x H (mm)	9,065 x 2,549 x 3,367 13,497 x 3,290 x 4,250
Track – L x B x H (mm)	6,940 x 2,854 x 3,268 11,372 x 3,290 x 4,151

Weight (dependent on equipment)

Hook (t)	21	21	21.3	21.3	21.7	21.7
Trailer (t)	23.3	23.3	23.5	23.5	23.9	23.9
Track (t)	24.4	24.4	24.6	24.6	25	25

Throughput (dependent on material)

Throughput (t/h)	up to 45	up to 45	up to 60	up to 60	up to 100	up to 120
in oughput (c/n)			up to 00	up to 00	up to 100	up to 120

Trailer (3-axle trailer)



Track (tracked chassis)





Never waste an opportunity



249 Union Street Westfield, MA 01085 www.SimplicityNE.com 800.553.6190

We create value for you



Waste-stream expertise

Because you need a setup that is tailored to your waste stream.

Ć.

Innovative technology

Because you need to adapt your output to your market needs.

		~
	\sim	N 1
Δ.	_	

Flexible sales models

Because you have the choice between new, rental and used machines.

	SQ3
	~~~
50	75
5	~~

#### Service excellence

Because you always need to keep your system running.

#### komptech.com